

## MOBILE WIND AND SOLAR ENERGY AGGREGATE

The present invention relates to a mobile power station having a transportable housing.

5 Mobile power stations having a transportable housing in which they are housed are known. Consideration can be given, for example, to a diesel generator that can be mounted on a trailer or lorry.

Mobile power stations of this type are used in particular for generating energy, in particular electrical energy, in locations where there is no connection to the mains power supply. The disadvantage of the known mobile power stations is, however, that these use 10 fossil fuels, such as diesel oil, for generating electricity and that during the combustion of these fossil fuels exhaust gases are produced which are released into the environment and thus introduce harmful or at least undesirable substances into the environment.

The aim of the present invention is, in particular, to provide a mobile power station 15 that is of universal applicability and is able to generate sustainable energy everywhere, without there being a need for a mains power supply to be present, and which can continue to supply electrical energy autonomously even in the absence of external energy sources, such as wind and sun, and the absence of any other external energy supply.

The abovementioned aim is achieved according to the invention with a mobile power 20 station having a transportable housing provided with:

- a wind turbine and/or
- a solar cell panel containing solar cells and
- storage means for storing electrical energy and delivering electrical energy,

wherein the wind turbine and the solar panel, respectively, are actively connected to the 25 storage means for supplying electrical energy generated by the wind turbine and the solar panel, respectively, to said storage means,

wherein the storage means comprise a battery and a hydrogen system, and

wherein the hydrogen system comprises a hydrogen generator, a hydrogen tank, actively connected to the hydrogen generator, for storing hydrogen produced using the hydrogen 30 generator, and a hydrogen cell, actively connected to the hydrogen tank, for generating electrical energy by combustion of hydrogen, or, to put it more accurately, oxidation of hydrogen to give water. The hydrogen cell, which is also termed a fuel cell, contains a membrane that ensures that the H<sub>2</sub> gas bonds with the O<sub>2</sub> gas by means of a redox reaction,

a reaction in which a stream of electrons from  $2 \times \text{H}_2 + \text{O}_2$  gives  $2 \times \text{H}_2\text{O}$ . Both the  $\text{H}_2$  and the  $\text{O}_2$  undergo a transition from neutral particles to electrically charged particles which release ions during their transition.

Where mention is made of combustion in this application this refers in particular to oxidation of hydrogen to give water. This can also be referred to as chemically controlled conversion of hydrogen to water.

The mobile power station according to the invention is capable of generating electrical energy by means of the wind turbine and/or the solar cell panel and of supplying this electrical energy to a consumer. If the consumer does not require the generated electrical energy immediately, or if the generated electrical energy is in excess of the requirement at that point in time, the mobile power station according to the invention is able to store this generated electrical energy in the storage means in order subsequently to be able to supply this energy when there is demand for the electrical energy but there is no wind and/or sun for generating electrical energy by means of the wind turbine or the solar panel, respectively, or when the demand for electrical energy is higher than the amount of energy that can be produced at that point in time by the wind turbine or the solar panel, respectively. To this end the storage means comprise a battery and a hydrogen system. The battery, which, of course, can consist of a number of accumulators, has the disadvantage that it takes up a relatively large volume but has the advantage that it is able to supply electrical energy immediately when this is required. The hydrogen system is capable of forming a much larger energy buffer. To this end this hydrogen system comprises a hydrogen generator which decomposes water into hydrogen and oxygen by means of electric power supplied to it. Such a hydrogen generator can be a so-called caustic potash decomposition unit. The hydrogen system further comprises a hydrogen tank for storing the hydrogen produced by the hydrogen generator. Hydrogen can then be taken off from the hydrogen tank when there is a demand for electrical energy, in order to supply this hydrogen to a hydrogen cell in which the hydrogen is burned with the generation of electrical energy. The combustion of hydrogen is a clean combustion or 100% clean chemically controlled conversion of hydrogen to water, which has hardly any or no associated disadvantages for the environment. The battery will preferably also be actively connected to the hydrogen cell in order to be able to bring this hydrogen cell into operation from stationary when there is a demand for electrical energy. A mobile power station of this type can relatively easily, on the one hand, be so designed that it can be accommodated

in its entirety in, for example, a 40 foot sea container and, on the other hand, is capable of providing a household with adequate electrical energy.

A mobile power station according to the invention will advantageously further comprise a solar collector panel that is actively connected to a boiler for hot water. In this way the mobile power station is also capable of supplying hot water, the water being heated in the boiler by the heat captured in the solar collector panel, and of dispensing water to be heated in said boiler. This entire unit can also still easily be accommodated in the said 40 foot container, whilst the capacity to supply hot water is adequate for an average household.

In order to allow the mobile power station to operate autonomously, it is preferable according to the invention if this has a water tank for rainwater, which water tank is actively connected via a filter system, preferably of the membrane type, to the hydrogen generator as well as preferably also to the boiler. In this way connection of the mobile power station to the water supply is superfluous and except in the case of inadequate rainfall a water supply can be completely dispensed with.

According to an advantageous embodiment of the invention, the transportable housing is a container, such as a 20, 30 or 40 foot freight container or a 20, 30 or 40 foot sea container. Such containers are relatively inexpensive and readily available and have the very significant advantage that because of their standard dimensions they can easily be placed on lorries, trains and ships and transported to their destination.

The wind turbine can be erected separately from the housing. However, with a view to simple, rapid and reliable erection of the mobile power station at the destination, it is preferable if the wind turbine is mounted on the housing and extends upwards from the roof of the housing, or at least can be brought into an active position extending upwards from the roof of the housing. With this arrangement the wind turbine, in particular the column on which the rotor is mounted, can extend through the roof of the housing in order to be fixed to the base of the housing or some other interior housing. In order, on the one hand, to obtain a transportable housing that is easy to manhandle and, on the other hand, a housing that is stable in the position ready for use, it is preferable according to the invention if the housing has a block-shaped base frame and if extendable supports are provided on opposite sides, in particular opposite longitudinal sides, of the housing. The extendable supports, which can also be provided with jacks to enable level support on the ground, ensure that the housing cannot be blown over as a result of the wind turbine on top

of it.

According to the invention the storage means will advantageously be accommodated in the housing and the housing will be provided with vents. These vents serve to ensure that any gases escaping from the battery or the hydrogen system are discharged to the outside in order to prevent explosive gas mixtures occurring in the housing.

So that the solar energy can be utilised in as optimum a manner as possible, it is preferable if the solar cell panel and/or the solar collector panel are/is, or at least can be, mounted on hinges on the outside of the housing. It is optionally conceivable to accommodate the solar cell panel and/or the solar collector panel in the housing during transport in order to prevent them from being damaged. The hinged mounting makes it possible to angle the solar cell panel and/or the solar collector panel towards the sun. With this arrangement it is optionally also readily conceivable for a control device also to be coupled to the solar cell panel and/or the solar collector panel, which control device is equipped to allow the solar cell panel or solar collector panel to follow the position of the sun in the sky.

The present invention will be explained in more detail below with reference to an illustrative embodiment shown diagrammatically in the drawing. In the drawing:

Fig. 1 shows a highly diagrammatic, perspective view of the exterior of a mobile power station according to the invention; and

Fig. 2 shows a highly diagrammatic, perspective view of the interior of a mobile power station according to the invention.

Figs 1 and 2 show an example of an embodiment, and specifically a preferred embodiment, of a mobile power station according to the invention.

The mobile power station shown comprises a transportable housing in the form of a 40 foot sea container 1 with conventional corner castings 28 and two doors 15 at one end. Configuration of the mobile power station in and on such a container 1 has the major advantage that this makes it possible to transport the mobile power station using means already available for the transport of such sea containers.

The mobile power station is provided on the roof with a wind turbine 2, 3, 4 which can be held upright by a guy wire 13 and which can be lowered in the longitudinal direction of the container 1 to lie in support 8 in a horizontal position. The wind turbine comprises a

telescopic column 2, 3, which when erected in the use position extends upwards from the roof of the container, with a wind turbine head provided with rotor blades 4 thereon.

The container 1 is provided with a panel 10 on one longitudinal side and optionally on two longitudinal sides. This panel 10 is a solar cell panel. This solar cell panel can be opened out with respect to the adjacent longitudinal wall of the container 1 by means of a boom 14, whilst this panel hinges about a hinge 29 running in the longitudinal direction of the container 1. The boom 14 can form part of a control device, which is equipped to be able to adjust the angle of the solar cell panel 10 with respect to the vertical as a function of the position of the sun in the sky. By designing the extender mechanism 14 in a suitable manner it is also conceivable that the solar cell panel 10 is opened outwards by more than 90° about hinge axis 29 in order to be facing the sun should this be on the right-hand side of the page of the drawing.

A solar collector panel 9 is provided on the roof of the container 1, which panel can be brought into an angled position directed towards the sun by means of extender arms 12, for example telescopic extender arms 12. These solar collector panels 9 are joined to the container 1 by means of hinges along a hinge axis 30 that extends in the longitudinal direction of the container 1. It should be clear that several solar collector panels 9 can have been provided on the roof of the container 1 and also that it is conceivable that several solar cell panels 10 can have been provided on one longitudinal side of the container. It is also very readily conceivable to change over the position of the solar cell panels 10 and solar collector panels 9, to provide both solar cell panels 10 and the solar collector panels 9 on the roof of the container 1, to provide both solar cell panels 10 and solar collector panels 9 on one or two longitudinal sides of the container and to make other combinations thereof.

Vents 11, consisting of a vent opening and a cover placed over this to prevent ingress of rain, are also provided in the roof of the container 1.

In order to prevent the container 1 from being blown over or falling over, in particular when strong gusts of wind are acting on the wind turbine 1, a support system that can be swung out is provided on both longitudinal sides of the container 1. The support system 5 consists of two arms that can be pivoted about hinge axis 6 and meet at a common point and at that point are equipped with a jack 7 that is adjustable in the vertical direction. In Fig. 1 the support system 5 is shown in the transport position, in the sense that it is folded back against the longitudinal side wall of the container 1. It should be clear that this support system 5 can be swung through 90° or optionally more with respect to the container

wall.

The container 1 is provided on the outside, but can optionally also be provided on the inside, with a connection 26 for electrical energy, or to put it more accurately electric power, as well as a connection 27 for hot water.

- 5        With reference to Fig. 2, the following are accommodated inside the container 1:
- a tank 19 for storing hydrogen, H<sub>2</sub>,
  - a boiler 20 for producing and storing hot water,
  - a storage vessel 21 for rainwater, which, inter alia, can be collected by means of a gutter 16
  - 10      at the bottom of the solar cell panel 10 and is fed to the rainwater vessel 21 by means of a pump,
  - a hydrogen generator 22 with an oxygen discharge 23 and a hydrogen discharge 24 leading to the hydrogen tank 19,
  - a fuel cell 17 suitable for generating electrical energy from hydrogen supplied via line 25 from the tank 19,
  - 15      a battery 18 for storing and supplying electrical energy.

The mobile power station according to the invention is capable of producing electrical energy from the sun or the wind by means of the solar cell panel 10 provided with solar cells and/or the wind turbine 2, 3, 4, respectively, and supplying this electrical energy via connection 26 to a user and/or storing this electrical energy in the battery 18 and/or by

20      means of this electrical energy generating hydrogen in the hydrogen generator by electrolysis of suitably filtered rainwater, which hydrogen is fed via line 24 to the tank 19 for storage, as well as generating oxygen, which is discharged into the environment via line 23. The hydrogen stored in the tank 19 can be fed at a suitable point in time, depending on the demand for electrical energy, to the fuel cell 17 in order to generate electrical energy in

25      said fuel cell by combustion of the hydrogen, which electrical energy can then be supplied to the end user and/or can be fed to the battery 18 for storing in said battery 18. Electrical energy from the battery 18 and/or electrical energy originating from the wind turbine 2, 3, 4 or the solar cell panel 10 can be used to start up the fuel cell. It should be clear that for the purposes of the abovementioned active connections, the necessary cabling, in particular for

30      electrical leads, which is not shown, will have been laid and also that the necessary transformers, control systems, etc., which are not shown and are also not discussed further, will have been provided, which for a person skilled in the art are no more than obvious and standard.

The solar collector 9 and boiler 20, which can be regarded as optional, provide the possibility that the mobile power station is also able to meet the need for hot water. The water to be heated in the boiler 20 could originate from the rainwater store 21, after suitable filtering and, if necessary, suitable purification, but can also originate from a storage vessel, that is not shown, to be installed outside the container 1 or from the mains water supply. Water circulated through a loop will be heated in the solar collector 9 by the sun in order then to be fed to the boiler 20 and there to transfer heat, via a heat exchanger that is not shown, to the water contained in the boiler, in order, after heat transfer, to be returned to the solar collector 9 to absorb heat again from the sun.

An example will be given below with a few indicative values for a mobile power station according to the invention, which is suitable for meeting the needs of a household. These values are:

- the solar panel 10 will contain approximately  $24 \text{ m}^2$  of solar cells;
- the solar collector 9 will occupy a surface area of approximately  $12 \text{ m}^2$ ;
- the wind turbine can be a turbine with a power of 1.5 to 3 kW, such as, for example, approximately 2.5 kW;
- the hydrogen tank 19 can have a capacity of approximately  $5 \text{ m}^3$  and be able to withstand an operating pressure of approximately 25 bar;
- the water tank can have a capacity of approximately  $2 \text{ m}^3$ . In this example the water tank 21 containing rainwater has been sized mainly with regard to adequate capacity for the hydrogen generator. Surplus water, optionally after storage in an additional container that is not shown, can be used for flushing toilets, etc.

A mobile power station of this type can provide a household with electric power with a maximum peak load of approximately 5,000 watt when the sun is shining and wind is blowing at 6 m/s. As a consequence of the battery and the stored hydrogen, the mobile power station can also provide the household with electric power when there is no wind or sun. The battery 18, or a number of batteries 18, as well as the hydrogen system is useful for this purpose.

With regard to the hydrogen system, the following values may be mentioned in this example. When the hydrogen tank 19 is filled to 20 bar there is approximately  $100 \text{ m}^3$  hydrogen available for generating power. With a yield of the order of magnitude of 80%, this gives approximately 400 kWh power. This is more than adequate for two months power consumption by an average family, including the use of a dishwasher and a washing

machine.

If the mobile power station is provided with a suitable connection for this, the hydrogen from the hydrogen tank 19 can also be used to drive a vehicle, such as a car. The vehicle will then first store the hydrogen in its own tank, in order to be able to operate  
5 independently of the container 1.

Surplus electrical energy can optionally be supplied directly to the mains power supply.

For reasons of safety, detectors for, in particular, hydrogen will have been provided inside the container, as well as, optionally, detectors for gases originating from the battery,  
10 and warning systems coupled to said detectors or further safety measures for ventilation of the interior of the container.

The mobile power station according to the invention is regarded as a mobile unit and is thus MOVABLE PROPERTY (and not immovable property). Consequently under existing legislation planning permission is NOT required for this design and as a result it  
15 can be used on a large scale without going through official channels.

The container can be finished in brown and green colouring such that it does not produce a blot on the landscape in its surroundings. The pretty colour scheme will result in camouflage of the functionality and at a distance will create the impression of a garden shed.



**Claims**

1. Mobile power station having a transportable housing provided with:

➤ a wind turbine and/or

5 ➤ a solar cell panel containing solar cells and

➤ storage means for storing electrical energy and delivering electrical energy,

wherein the wind turbine and the solar panel, respectively, are actively connected to the storage means for supplying electrical energy generated by the wind turbine and the solar panel, respectively, to said storage means,

10 wherein the storage means comprise a battery and a hydrogen system, and

wherein the hydrogen system comprises a hydrogen generator, a hydrogen tank, actively connected to the hydrogen generator, for storing hydrogen produced using the hydrogen generator, and a hydrogen cell, actively connected to the hydrogen tank, for generating electrical energy by combustion of hydrogen.

15

2. Mobile power station according to Claim 1, containing a solar collector panel that is actively connected to a boiler for hot water.

3. Mobile power station according to Claim 1 or 2, containing a water tank for  
20 rainwater, wherein the water tank is actively connected via a filter system, preferably of the membrane type, to the hydrogen generator as well as preferably also to the boiler.

4. Mobile power station according to one of the preceding claims, wherein the transportable housing is a container, such as a 20, 30 or 40 foot freight or sea container.

25

5. Mobile power station according to one of the preceding claims, wherein the wind turbine is mounted on the housing and extends upwards from the roof of the housing, or at least can be brought into an active position extending upwards from the roof of the housing.

30

6. Mobile power station according to Claim 5, wherein the housing has a block-shaped base frame and wherein extendable supports are provided on opposite sides, in particular opposite longitudinal sides, of the housing.

7. Mobile power station according to one of the preceding claims, wherein the storage means are accommodated in the housing and wherein the housing is provided with vents.


5


8. Mobile power station according to one of the preceding claims, wherein the solar cell panel and/or the solar collector panel are/is, or at least can be, mounted on hinges on the outside of the housing.

10

\*\*\*\*\*

1/2

*Fig 1*

*Fig 2*

## INTERNATIONAL SEARCH REPORT

International Application No

PC 02/00481

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 F03D9/00 F03D9/02

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F03D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 94 20802 A (KONHA KONSTRUKTIONS UND HANDEL ;BOESSINGER HERBERT (DE); ANDRETO H) 15 September 1994 (1994-09-15)	1,2,4,5, 7,8
Y	abstract page 1, line 6 - line 11 page 2, line 16 -page 3, line 5 page 5, line 15 - line 26 page 7, line 6 - line 37; figure 1 page 8, line 13 - line 16 page 15, line 27 - line 34 claims 1,2,7,9	3,6
Y	DE 37 08 637 A (KRAUSE BERNHARD DIPL ING) 6 October 1988 (1988-10-06) the whole document	1,2,4,5, 7,8



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\* & \* document member of the same patent family

Date of the actual completion of the international search

27 September 2002

Date of mailing of the international search report

07/10/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Criado Jimenez, F

## INTERNATIONAL SEARCH REPORT

International Application No

PC 02/00481

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	DE 93 21 520 U (ZENON ENVIRONMENTAL INC) 29 July 1999 (1999-07-29)	3
A	page 1, paragraph 2 page 12, paragraph 1 page 25, paragraph 3 page 28, paragraph 5; figures	4
Y	DE 375 498 C (A. HOBUS) 15 May 1923 (1923-05-15) the whole document	6
A	DE 34 05 466 A (HOLZNER JOSEF) 22 August 1985 (1985-08-22) abstract; figures	1,2
A	FR 2 614 368 A (LEGER JEAN CLAUDE) 28 October 1988 (1988-10-28) abstract claims 1,2,4,9	1,3,4,6, 8
A	US 4 326 013 A (JACOBI EDGAR F ET AL) 20 April 1982 (1982-04-20) abstract column 1, line 50 - line 57	1,4
A	DE 196 46 612 C (ALBRECHT JOERG ;AHRENS REINER DIPL ING (DE)) 26 March 1998 (1998-03-26) abstract , sentence 51; figure	1,6
A	EP 0 515 329 A (BETHLEN DE BETHLEN MIKLOS ISTV) 25 November 1992 (1992-11-25) abstract; figures 4,5	7
A	EP 0 237 445 A (REDON DALMON S A) 16 September 1987 (1987-09-16) abstract; figures	4
T	DE 100 00 874 A (BRINKMANN KLAUS) 19 July 2001 (2001-07-19) abstract; figures 1,2	1,3

## INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP 02/00481

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9420802	A	15-09-1994	WO 9420802 A1	15-09-1994
DE 3708637	A	06-10-1988	DE 3704280 A1	25-08-1988
			DE 3708637 A1	06-10-1988
DE 9321520	U	29-07-1999	DE 9321520 U1	29-07-1999
			CA 2108023 A1	10-04-1994
			DE 69322361 D1	14-01-1999
			DE 69322361 T2	29-04-1999
			EP 0592372 A2	13-04-1994
DE 375498	C	15-05-1923	NONE	
DE 3405466	A	22-08-1985	DE 3405466 A1	22-08-1985
FR 2614368	A	28-10-1988	FR 2614368 A1	28-10-1988
US 4326013	A	20-04-1982	NONE	
DE 19646612	C	26-03-1998	DE 19646612 C1	26-03-1998
EP 0515329	A	25-11-1992	IT 1249740 B	11-03-1995
			DE 69205492 D1	23-11-1995
			EP 0515329 A2	25-11-1992
EP 0237445	A	16-09-1987	FR 2593206 A1	24-07-1987
			EP 0237445 A1	16-09-1987
DE 10000874	A	19-07-2001	DE 10000874 A1	19-07-2001